

Highlights:

- Spring-clamp mounting mechanism
- IP65 Ingress protection
- Multi-tapping 100V line transformer
- 4" dual cone driver
- plastic enclosure
- Aluminum grill

Product information:

The AWP06 is a waterproof ceiling speaker with a power of 6 Watt which meets the IP65 standard. It is designed to be used in a wide variation of in- and outdoor applications and damp locations and features a 4" loudspeaker. Due to its wide smooth frequency response and high efficiency, it ensures high-fidelity music reproduction and intelligible speech at very low distortion. It can be used in 8 Ohm low impedance systems or in 100V PA systems with power taps for 6 Watt, 3 Watt and 1.5 Watt.

Applications:

- null
- null



Certification:

 IP65

Properties:

 Weatherproof

Impedance:

 8 Ohm

Voltage:

 100 Volt

System specifications:

Peak power handling		20 W
Program power handling		10 W
Continuous power (AES)		6 W
Frequency	Response (± 3 dB)	100 Hz - 15 kHz
Sound Pressure (Max. W/1m)		95 dB
Line Transformer Tappings	1	null
	2	null
	3	null
Impedance		8 Ω
Ingress Protection rating		IP65
Drivers		4"
Dispersion		150°

Product Features:

Dimensions		5.51 x 5.85 " (\varnothing x H)
Built-in depth		5.85 "
Cut-out measurement		4.92 " (\varnothing)
Weight		1.74 lb
Operating temperature		-4 °F ~ 140 °F
Construction		ABS
Colours		White (RAL9010)
		White (RAL9016 - I version)

Variants:

- AWP06I/W - White version - RAL9016