



BASSO112

12" ultra-high power infra-subwoofer

Highlights:

- null
- null
- 2000 Watt program power
- null
- null

Product information:

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion.

Applications:

- null
- Clubs
- null
- Events
- Concert venues
- null
- Hotels



Impedance:

Ω 8 Ohm

Usage:



Indoor

System specifications:

Speaker type		null
Configuration		null
Peak power handling		4000 W
Program power handling		2000 W
Continuous power (AES)		1000 W
Impedance		8 Ω
Max SPL (Continuous/AES)		124 dB
Sensitivity (1W/1m)		94 dB
Frequency	Response (- 3 dB)	33 Hz - 120 Hz
	Range (-10 dB)	26 Hz - 200 Hz
Bass port tuning frequency		39 Hz
Drivers		12" carbon cone with dual suspension (low-loss) and 3.5" high excursion voice coil
Connectors		null

Product Features:

Dimensions		23.94 x 14.41 x 23.43 " (W x H x D) (excluding feet)
		23.94 x 14.61 x 23.43 " (W x H x D) (including feet)
Weight		57.32 lb
Operating temperature		-4 °F ~ 158 °F
Construction		18 mm Multiply plywood
		Coating - Multi-Layer polyurea coating (4-layer)
		Metal parts - Zinc plated bolts & fasteners
Front finish		2.0 mm Zinc plated steel with hexagon perforations and powder coat & acoustical foam backing
Mounting & handling	Rigging points	null
	Stand fitting	null
Colours		Black

Variants:

- BASSO112/B - Black version