

## Highlights:

---

- null
- IP55 Ingress protection
- 3000 Watt program power
- null
- 127 dB of Max. SPL
- Impact resistant, ball impact proof
- null

## Product information:

---

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion. Ready for any environment

For installations exposed to the elements, the BASSO/OB Series is specifically built to thrive outdoors without compromising performance. Every detail is enhanced to ensure durability in harsh conditions:

Weatherproof construction using 18 mm marine-grade plywood with phenolic resin glue for superior moisture resistance. Reinforced protection with an extra-thick 6-layer multi-layer polyurea coating, providing a rugged, UV- and impact-resistant finish. IP55 certified, ensuring reliable operation even in dusty or moist environments. Stainless steel bolts and fasteners resist corrosion for long-term durability. Advanced front grill design, combining a stainless steel mesh with powder coating, acoustical foam, and a hydrophobic mesh backing to protect the internal components without compromising audio transparency. Secure connectivity, featuring a high-current terminal block with link-through and a waterproof cover to safeguard signal integrity in any weather. Whether deployed in an open-air stage, outdoor bar, or theme park installation, the BASSO/OB models are built to endure and perform with the same clarity, depth and impact as their indoor counterparts.

## Applications:

---

- null
- Hotels
- Clubs
- null
- Events
- Concert venues
- null



## Properties:

---

 Weatherproof

## Impedance:

---

$\Omega$  8 Ohm

## Usage:



Indoor



Outdoor

## System specifications:

Speaker type		null
Configuration		null
Peak power handling		6000 W
Program power handling		3000 W
Continuous power (AES)		1500 W
Impedance		8 $\Omega$
Max SPL (Continuous/AES)		130 dB
Sensitivity (1W/1m)		98 dB
Frequency	Response (- 3 dB)	37 Hz - 120 Hz
	Range (-10 dB)	31 Hz - 200 Hz
Bass port tuning frequency		38 Hz
Drivers		15" carbon cone with dual suspension (low-loss) and 4" high excursion voice coil
Ingress Protection rating		null
Connectors		null

## Product Features:

Dimensions		27.087 x 17.56 x 27.68 " (W x H x D) (excluding feet)
		27.087 x 17.76 x 27.68 " (W x H x D) (including feet)
Weight		77.16 lb
Operating temperature		-4 °F ~ 158 °F
Construction		18 mm Multiply marine-grade plywood (with phenolic resin glue)
		Coating - Extra-thick Multi-Layer polyurea coating (6-layer)
		Metal parts - Stainless steel bolts & fasteners
Front finish		2.5 mm Stainless steel with hexagon perforations, powder coat, acoustical foam & stainless hydrophobic mesh backing
Mounting & handling	Rigging points	null
Colours		Black

## Variants:

---

- BASSO115/OB - Outdoor black version