

BASSO118_O

Outdoor 18" ultra-high power infra-subwoofer

Highlights:

- null
- IP55 Ingress protection
- 3000 Watt program power
- null
- 128 dB of Max. SPL
- Impact resistant, ball impact proof
- null

Product information:

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion. Ready for any environment

For installations exposed to the elements, the BASSO/OB Series is specifically built to thrive outdoors without compromising performance. Every detail is enhanced to ensure durability in harsh conditions:

Weatherproof construction using 18 mm marine-grade plywood with phenolic resin glue for superior moisture resistance. Reinforced protection with an extra-thick 6-layer multi-layer polyurea coating, providing a rugged, UV- and impact-resistant finish. IP55 certified, ensuring reliable operation even in dusty or moist environments. Stainless steel bolts and fasteners resist corrosion for long-term durability. Advanced front grill design, combining a stainless steel mesh with powder coating, acoustical foam, and a hydrophobic mesh backing to protect the internal components without compromising audio transparency. Secure connectivity, featuring a high-current terminal block with link-through and a waterproof cover to safeguard signal integrity in any weather. Whether deployed in an open-air stage, outdoor bar, or theme park installation, the BASSO/OB models are built to endure and perform with the same clarity, depth and impact as their indoor counterparts.

Applications:

- null
- Hotels
- Clubs
- null
- Events
- Concert venues
- null



Properties:

 Weatherproof

Impedance:

Ω 8 Ohm

Usage:



Indoor



Outdoor

System specifications:

Speaker type	null	
Configuration	null	
Peak power handling	6000 W	
Program power handling	3000 W	
Continuous power (AES)	1500 W	
Impedance	8 Ω	
Max SPL (Continuous/AES)	131 dB	
Sensitivity (1W/1m)	99 dB	
Frequency	Response (- 3 dB)	30 Hz - 120 Hz
	Range (-10 dB)	23 Hz - 200 Hz
Bass port tuning frequency	33 Hz	
Drivers	18" carbon cone with dual suspension (low-loss) and 4" high excursion voice coil	
Ingress Protection rating	null	
Connectors	null	

Product Features:

Dimensions	29.84 x 21.65 x 31.42 " (W x H x D) (excluding feet)	
	29.84 x 21.85 x 31.42 " (W x H x D) (including feet)	
Weight	99.21 lb	
Operating temperature	-4 °F ~ 158 °F	
Construction	18 mm Multiply marine-grade plywood (with phenolic resin glue)	
	Coating - Extra-thick Multi-Layer polyurea coating (6-layer)	
	Metal parts - Stainless steel bolts & fasteners	
Front finish	2.5 mm Stainless steel with hexagon perforations, powder coat, acoustical foam & stainless hydrophobic mesh backing	
Mounting & handling	Rigging points	null
Colours	Black	

Variants:

- BASSO118/OB - Outdoor black version