

## Highlights:

---

- Multi-functional wall bracket allowing swiveling and down-tilting
- Slimline aluminum design
- 12 x 2" high-quality broadband speakers
- null

## Product information:

---

The KYRA12 design column speaker consists of 12 x 2" high-quality aluminum cone full-range drivers, delivering extraordinary clarity and detailed sound. The overall continuous power handling reaches 120 Watt and the beamwidth of 174° x 9° (-6 dB avg 1 kHz - 4 kHz)\* makes it the perfect match for acoustically difficult venues, reducing echo and microphone feedback which optimizes the speech intelligibility in reverberant venues.

A multi-tapping line transformer allows it to be connected to 70V/100V public address systems with different power taps for 40W, 20W and 10W and/or low impedance (12Ω) systems.\*\*

\*Given dispersion values are the average beamwidth within the 1 kHz - 4 kHz frequency range (-6 dB - 1/3 oct), which are critical for the speech intelligibility in the main application field of these loudspeakers.

\*\*Due to an optimized calibration, the KYRA12, compared to its predecessor the AXIR, will have a standard low impedance of 12 ohms instead of 6 ohms.

## Applications:

---

- Education
- null
- Houses of worship
- Events



## Impedance:

---

Ω 12 Ohm

## Voltage:

---

⚡ 70-100 Volt

## System specifications:

Speaker type		Broadband column
Peak power handling		480 W
Program power handling		240 W
Continuous power (AES)		120 W
Impedance		12 $\Omega$
Sensitivity (1W/1m)		92 dB
Max SPL (Continuous/AES)		113 dB
Max SPL (Program)		116 dB
Max SPL (Peak)		119 dB
Frequency	Range (-10 dB)	120 Hz - 20 kHz
	Response ( $\pm$ 3 dB)	150 Hz - 20 kHz
Drivers		12 x 2"
Line Transformer Tappings	1	40 W - 125 $\Omega$ (70V)
	2	250 $\Omega$ - 100 V / 40 W - 70 V / 20 W
	3	500 $\Omega$ - 100 V / 20 W - 70 V / 10 W
	4	1000 $\Omega$ - 100 V / 10 W - 70 V / 5 W
Ingress Protection rating		IP3x
Temperature	Operating	-4 - 122 $^{\circ}$ F
Incline angle	Left	42 $^{\circ}$
	Right	42 $^{\circ}$
	Bottom	13 $^{\circ}$
Dispersion	Horizontal	174 $^{\circ}$ (-6 dB avg 1 kHz - 4 kHz)
	Vertical	9 $^{\circ}$ (-6 dB avg 1 kHz - 4 kHz)

## Product Features:

Front finish		Steel grill
Construction		Aluminium with plastic side covers
Dimensions		2.76 x 39.61 x 3.98 " (W x H x D)
Colours		Black (KYRA12/B - RAL9005)
		White (KYRA12/W - RAL9003)
Accessories	Included	2-way Revolving mounting bracket
		1 x 3-pin Euro Terminal Block Input connectors

## Variants:

---

- KYRA12/B - Black version
- KYRA12/W - White version