

## Highlights:

---

- null

## Product information:

---

The LUNA-U is the next-generation audio matrix processor, offering highly flexible and scalable system solutions for audio distribution from medium-sized to the largest enterprise solutions. The internal structure provides unseen flexibility and a vast number of possibilities for an audio distribution system. The powerful DSPs (dual SHARC) combined with 32-bit ADC and DAC converters allow the most extensive signal processing with superb audio quality.

It includes 12 Mic/Line Inputs and 8 Line level outputs. Additionally, up to 32 Dante™/AES67 I/O Channels are available with a single ethernet port, allowing the integration of the system with any Dante™/AES67 compatible audio over IP I/O unit.

The flexible architecture allows fully flexible mapping of the signal path to any of the 32 mono or 16 stereo zones, while the powerful DSP resources provide unique processing features on all input channels, output channels, and zones. Dante-enabled paging microphones and smart wall panels make the complete system solution even more flexible and unique.

The internal Linux core provides the entire control of the LUNA series while also accommodating messaging, event scheduling, and implementation possibilities for future Linux-based functions. In addition to full network control, RS-232 and RS-485 interfaces are available for receiving third-party serial communication. For your system solution, you can easily incorporate the control of the entire system and compatible devices into your user interface by using our simplified design and system control platform, AUDAC Touch™.

## Applications:

---

- null
- null
- Hotels
- null
- Education
- null



## Certification:

---



## Additional Inputs:

---



## System specifications:

|                       |                                    |              |
|-----------------------|------------------------------------|--------------|
| Inputs                | Mic / Line inputs                  | 12           |
|                       | GPIO Inputs                        | 12 (in)      |
|                       | USB Inputs (Type C)                | null         |
|                       |                                    | null         |
| Outputs               | Line outputs                       | 8            |
|                       | GPIO Outputs                       | 12 (out)     |
|                       | Fault                              | null         |
| Network audio I/O     |                                    | null         |
| Zones                 |                                    | null         |
| Configurable settings | ALC (Automatic Gain control)       | Yes          |
|                       | AEC (Acoustic Echo cancellation)   | No           |
|                       | Integrated event scheduler         | Yes          |
|                       | Phantom power on inputs            | null         |
|                       | WaveTune (input & zone)            | null         |
|                       | WavePreset (output)                | null         |
|                       | Delay (output)                     | 2000 ms      |
|                       | Mono / stereo zones (configurable) | Yes          |
|                       | Mixing                             | Yes          |
|                       | Talkover                           | Yes          |
|                       | Paging                             | Yes          |
|                       | Priorities                         | null         |
|                       | Integrated generator               | null         |
|                       | Output Volume offset               | Yes          |
| Others                | null                               |              |
| DSP Processor         |                                    | null         |
|                       |                                    | null         |
| Configuration         |                                    | Audac Touch™ |
| Controls & indicators | Front panel                        | null         |
|                       | Interface ports                    | RS-232       |
|                       |                                    | RS-485       |
|                       |                                    | null         |

Power

Supply

100 ~ 240 V AC / 50 ~ 60 Hz

24 V DC

## Product Features:

---

Dimensions

18.98 x 1.73 x 13.19 " (W x H x D)

Mounting

19"

Unit height

1 HE

Construction

Steel

Colours

Black (RAL9005)