

Highlights:

- 320 Watt program power
- null
- null
- Integrated advanced protection circuit
- SnapConnect™ enabling a fast and reliable connection
- null
- null

Product information:

The VIRO-C series delivers compact line array performance in an ultra-slim architectural form. Designed for precise speech intelligibility and consistent high SPL coverage, VIRO-C is ideal for high-end corporate spaces, retail environments, residential interiors, and yachting applications where sound quality and aesthetics must align seamlessly.

Featuring custom engineered 1.3 inch drivers, precise pattern control, and a wide 160 degree horizontal dispersion, the VIRO-C series ensures predictable in room performance with excellent clarity throughout the space. The aluminum housing supports ThermalDrive protection, maintaining stable operation under continuous load, while the integrated protection circuit safeguards long term reliability.

With a tool free click on grill, Snapconnect wiring, internal impedance switching, and versatile mounting options including a flush mount solution in development, the VIRO-C series combines refined installation with powerful, controlled sound in a discreet architectural design.



Impedance:

Ω 8 Ohm Ω 16 Ohm

Usage:



Indoor

System specifications:

Speaker type	Column speaker
Continuous power (AES)	160 W
Program power handling	320 W
Peak power handling	640 W
Impedance	4 / 16 Ω
Sensitivity (1W/1m)	92 dB
Sound Pressure (Max. W/1m)	114 dB
Sound Pressure (Peak dBZ, crest factor 4 = +12dB)	132 dBZ
Frequency	Range (-10 dB)
Dispersion	Horizontal
	Vertical
Drivers	16 x 1.3"
Temperature	Operating

Product Features:

Front finish	Powder coated fine perforated steel
Construction	Alu extrusion
Dimensions	1.65 x 26.77 x 1.36 " (W x H x D)
Weight	3.31 lb
Colours	Black (VIRO-C1601/B) White (VIRO-C1601/W)

Variants:

- VIRO-C1601/B - Black version
- VIRO-C1601/W - White version