

Highlights:

- Warm & true to nature sound
- Weatherproof - IP55 rating
- Countless mounting possibilities
- null
- High grade aluminum construction
- 70V/100V transformer option available

Product information:

"A sound that lasts"

The VIRO is a powerful 2-way performance speaker which is designed for outdoor and indoor use, ensuring true-to-nature, high fidelity reproduction of music and speech in every environment, ranging from residential applications to the most demanding outdoor applications in parks, hotels and even clubs.

Crafted in high-grade aluminium with incredible attention to detail. The material choice goes well beyond aesthetics. It also provides superior acoustic properties thanks to its material stiffness and seamless surfaces that eliminate any distortion of your sound.

The aluminium construction and grill with hydrophobic cloth provides the necessary protection for all weather conditions. The combination of the cloth, sealing rubbers and drainage holes on the bottom of the speaker make it IP55 compliant (Successfully endured 720h salt spray test).

Exchange your connections easily. From cable glands with rubber grommets to optional SpeakON connections and even an optional 70/100V transformer (TRV106).

Applications:

- null
- Clubs



Certification:

 IP55

Properties:

 Weatherproof

Impedance:

Ω 8 Ohm Ω 16 Ohm

Voltage:

 70-100 Volt

System specifications:

Speaker type	Compact performance 2-way coaxial	
Peak power handling	240 W	
Program power handling	120 W	
Continuous power (AES)	60 W	
Impedance	8 Ω (VIRO5)	
	16 Ω (VIRO5D)	
Sensitivity (1W/1m)	89 dB	
Sound Pressure (Max. W/1m)	110 dB	
Frequency	Range (-10 dB)	50 Hz - 20 kHz
Dispersion	Conical	160° (average 500 Hz to 5 kHz @ -6 dB)
Drivers	HF	Soft dome treated silk 1"
	LF	5 1/4" Treated paper
Connectors	4-pin Euro Terminal Block	
Ingress Protection rating	IP55	
Outdoor resistance	null	

Product Features:

Dimensions		7.80 x 9.25 x 7.52 " (W x H x D) (Incl. bracket)
		7.087 x 7.087 x 7.52 " (W x H x D) (Excl. bracket)
Mounting	Mounting pattern	null
Mounting & handling	Stand fitting	null
Construction		Textured powder coated aluminium 4 mm
Front finish		null
Colours		White (RAL9003) (VIRO5/W & VIRO5D/W)
		Black (RAL9005) (VIRO5/B & VIRO5D/B)
Weight		9.26 lb
Accessories	Included	Mounting bracket
		null
		Connection plate with cable grommit
	Optional	null
		null

Variants:

- VIRO5/B - Black version - 8Ω
- VIRO5/W - White version - 8Ω
- VIRO5D/B - Black version - 16Ω
- VIRO5D/W - White version - 16Ω