

Highlights:

- 1" Dome tweeter
- 3" Low frequency loudspeaker
- Vertical and horizontal mounting
- Aluminum grill
- Aluminum mounting bracket (MK2 version)
- Multi-tapping 100V line transformer
- AWX5™ waterproof connector
- null

Product information:

The WX302/O speakers are specifically designed for outdoor use and lend themselves to a variety of applications, ensuring true-to-nature, high-fidelity reproduction of music and speech.

The material used for the mounting bracket on the outdoor versions has been improved by using aluminum, making the WX series MK2 even more resistant to extreme weather conditions. The bracket allows users to mount the WX302/O vertically as well as horizontally.

Special treatment with powder coating provides the necessary protection for all weather conditions. Because of the special powder coating, the brackets can pass the 96 hours salt-spray test, which has reached the standard for outdoor applications. A drain hole behind the aluminum grill allows rainwater to flow out. The waterproof AWX-5 connector at the backside makes sure that this speaker meets the IP55 standards.

Applications:

- null
- Retail
- null
- null
- null



Certification:

 IP55

Properties:

 Weatherproof

Impedance:

 8 Ohm

Voltage:

 70-100 Volt

System specifications:

Connectors		Waterproof AWX-5 connector
Crossover	Frequency	2.5 kHz
	Type	Passive built-in
Drivers	HF	1"
	LF	3"
Frequency	Range (-10 dB)	60 Hz - 20 kHz
	Response (± 3 dB)	90 Hz - 18 kHz
Impedance		8 Ω
Ingress Protection rating		IP55
Peak power handling		120 W
Program power handling		60 W
Sensitivity (1W/1m)		85 dB
Sound Pressure (Max. W/1m)	@ 100 V	95 dB
	@ 8 Ω	100 dB
Speaker type		2-way
Continuous power (AES)		30 W
Dispersion	Horizontal	100°
	Vertical	100°
Line Transformer Tappings	1	250 Ω - 100 V / Not used - 70 V / 20 W
	2	500 Ω - 100 V / 20 W - 70 V / 10 W
	3	1000 Ω - 100 V / 10 W - 70 V / 5 W

Product Features:

Dimensions		7.83 x 5.079 x 4.72 " (W x H x D)
Weight		3.66 lb
Operating temperature		-13 °F ~ 158 °F
Construction		ABS
Mounting & handling		Mounting bracket
Front finish		Aluminium grill
Colours		Black (RAL9005) (WX302MK2/OB)
		White (RAL9003) (WX302MK2/OW)
Accessories	Included	Mounting bracket
		null
	Optional	AWC07 - AWX5 cable 0.7 m
		AWC25 - AWX25 cable 2.5 m
		AWC50 - AWX50 cable 5 m

Variants:

- WX302MK2/OB - Outdoor black version
- WX302MK2/OW - Outdoor white version