

Highlights:

- Fully flexible modular structure
- 4 x SourceCon™ interface card slots
- 2.8" LCD display with intuitive user interface
- Wide variation of modules separately available
- Front USB interface for each module (4x)
- Remote control web interface (HTML5)
- RS232 & TCP/IP control port
- Front PFL speaker with vol. control
- Simultaneous operation for all modules

Product information:

The XMP44 is a professional modular audio system with 4 SourceCon™ interface card slots where to a wide variation of optional modules can be installed. The variety of available modules ranges from FM tuners to DAB&DAB+ tuners, internet radio tuners, voice file interfaces and many more. The flexible architecture allows any project combination up to four sources, resulting in a truly versatile solution that will live up to the needs for any user taking high regard of crystal clear audio reproduction. Simultaneous operation for all four modules makes it a compact multi-source system which is the perfect expansion for any multi-zone audio system. The front panel of the system accommodates a 2.8" TFT display in combination with a push rotary function dial and 4 tactile pushbuttons. The controls and indicators on the front panel of the unit are guaranteeing an intuitive and user friendly operation, allowing hassle free operation and configuration to even unexperienced users. Four USB interfaces (one for each module) are enabling playback or storage of media and voice file, while pre-listening for each output is possible through a built-in PFL speaker with individual volume control. Both RS-232 and TCP/IP communication ports are implemented, allowing system integration with any home or industrial automation system. Using the freely available AUDAC Touch™ application for smart devices guarantees total system control and configuration from any device on any location and at any time. An optional Dante™ interface is available for the XMP44. The installation of this network interface allows receiving and sending of low latency, high quality audio over a standard Ethernet network.

Discover more about our modular audio players
Choose your native platform and get started!

[Download for Android](#)

[Download for Apple iOS](#)



Certification:



Additional Inputs:



Applications:

- null
- null
- Education
- Clubs
- Retail
- Houses of worship

System specifications:

Inputs	Type	4 x SourceCon™ interface card slots
		4 x USB interface
Control		Front panel
		RS-232
		TCP/IP
		Audac Touch™
		Web (HTML5)
Frequency	Response (± 3 dB)	20 Hz - 20 kHz
Display	Type	2.8" Graphical LCD
Monitoring		Front PFL speaker with vol control
Power	Source	110 ~ 240 V AC / 50 ~ 60 Hz
	Consumption	2 W (without module installed)
	Supply	Switching mode
Operating temperature		0° ~ 40° @ 95% Humidity
Socket Connections (AUDAC Touch™)		4 sockets

Product Features:

Dimensions	18.98 x 1.73 x 12.99 " (W x H x D)
Weight	7.50 lb
Mounting	19"
Unit height	1 HE
Construction	Steel
Colours	Black