

# CCT60U-CCA

Networking cable - CAT6 - U/UTP - solid 0.25 mm<sup>2</sup> - 23 AWG - EN50399 CPR Euroclass Cca-s1a,d1,a1

## Highlights:

---

- EN50399 CPR Euroclass Cca-s1a,d1,a1
- 250 Mhz performance, up to 1000Base-T
- "+" Shaped separator to reduce crosstalk

## Product information:

---

The CCT60U-Cca is a CAT6 installation networking cable compliant to the Cca standard of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its improved fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The cable consists of 4 twisted pair cables with solid 23 AWG conductors and a "+" shaped separator. This way, crosstalk and system noise is reduced to a minimum, resulting in higher bandwidth and improved immunity against noise and interference caused by external devices. Providing an optimized solution for 10Base-T, 100Base-TX and 1000Base-T gigabit networks.

More information about CPR compliant cables? [Click here](#)



## Certification:

---



## Properties:

---



## Inner Conductors:

---



Product Features:

Application	null
Series	null

Physical Characteristics:

Type of cable		U/UTP CAT6 Networking cable		
EN50399 CPR Euroclass		Cca-s1a,d1,a1		
Inner conductor	Material	BC 1 x 0.56 mm (Ø) (OFC)		
	Section	0.00039 "²		
	American Wire Gauge	23 AWG		
	Insulation	Colours	Green / White & Green ; Blue / White & Blue ; Orange / White & Orange ; Brown / White & Brown	
		Material	HDPE 0.038 " (Ø)	
	Number of conductors		8 (4 pairs)	
	Conductor twisting		Yes	
Separator		+ shaped separator		
Outer jacket	Material	LSHF 6 mm (Ø)		
	Colours	Black		

Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
CPR Euroclass	Cca-s1a,d1,a1
Flammability test	According EN 60332-1-2
Indoor / outdoor	UV resistant (UL1581, UVA, 720 h)
Smoke emissions	According IEC 61034
Zero halogen compounds	According EN 50267-2-1
	IEC 60754

Electrical Characteristics:

Max. conductor	DC resistance	8.2 Ω / 100 m
	DC resistance unbalanced	< 2 %
Max. Delay / Skew	<45 (ns / 3937.0079 ")	
Rated voltage	300 V	
Nom. Velocity of propagation	69 %	
Characteristic impedance	100 Ω ± 15 Ω	
Nom. mutual capacitance	≤ 5.6 (nF / 100 m)	
Pair to ground capacitance unbalance	≤ 160 (pF / 100 m)	

Mechanical Characteristics:

Temperature range	Fixed installation	- 41 °F till + 176 °F
	Mobile installation	- 59 °F till + 176 °F
UV resistant	Yes	

Cross sections:

---

