

CHD124

HDMI cable - solid 0.20 mm² - 24 AWG - FlamoFlex™

Highlights:

- FlamoFlex™ IEC 60332-1 installation jacket
- Triple shielding

Product information:

The CHD124 is an high speed HDMI cable with Ethernet, designed for on-site termination with HDM19 connectors. It features a FlamoFlex™ outer jacket compliant to the IEC 60332-1 standard regarding fire and flammability resistance in public installations. The FlamoFlex™ material is specifically designed with installers convenience in mind, offering a smooth and durable outer jacket for easy installation and pulling. The conductor section of the CHD124 consists of 5 individually shielded pairs with solid 24 AWG conductors for transferring both video and Ethernet data. An additional 26 AWG pair and two separate 26 AWG conductors are used for synchronization between transmitter and receiver. This entire section is additionally covered with a double shielding consisting of an overall aluminum foil surrounded by a braiding. The triple shielding offers a high immunity against noise and interference caused by external devices. Using the CHD124, high definition video (1080p) can be transferred over distances up to 20 meters, Lengths below 10m will perform as HIGH SPEED HDMI with ETHERNET and Lengths between 10 and 15m will perform at STANDARD SPEED HDMI with ETHERNET standards.. Compatible with PROCAB connector HDM19.



Certification:



Properties:



Inner Conductors:



Shielding:



Product Features:

Series	null
--------	------

Physical Characteristics:

Inner conductor	Insulation	Material	FM-PE 1.4 mm (Ø) (5 pair)
			HD-PE 0.9 mm (Ø) (1 pair)
			HD-PE 0.9 mm (Ø) (2 cond.)
	Shielding	Aluminium foil	null
		Drain wire	BC 1 x 0.511 mm (Ø) (OFC)
Overall shielding	Aluminium foil		null
	Drain wire		BC 1 x 0.511 mm (Ø) (OFC)
	Braiding		AL-MG 16 x 12 x 0.12 mm (Ø)
Inner conductor	Material		BC 1 x 0.511 mm (Ø) (OFC) (5 pair)
			TC 7 x 0.16 mm (Ø) (OFC) (1 pair)
		American Wire Gauge	24 AWG (5 pair)
			26 AWG (1 pair)
			26 AWG (2 cond.)

Mechanical Characteristics:

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 59 °F till + 140 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter