

CLS215-CCA

Loudspeaker cable - 2 x 1.5 mm² - 16 AWG - EN50399 CPR
Euroclass Cca-s1b,d0,a1

Highlights:

- EN50399 CPR Euroclass Cca-s1b,d0,a1
- 16 AWG (1.5 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant

Product information:

The CLS215-Cca series are 2-core installation loudspeaker cables compliant to the Cca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire. In addition to its improved fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling.

The CLS2xx series consists of three models with individually polyolefin isolated conductors in sections ranging from 1.5 mm² (16 AWG) up to 4 mm² (11 AWG) which are composed of stranded bare copper wires. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.


More information about CPR compliant cables? [Click here](#)



Certification:



Properties:





Product Features:

Application	null
Series	null

Physical Characteristics:

Type of cable	2-core loudspeaker cable	
EN50399 CPR Euroclass	Cca-s1b,d0,a1	
Inner conductor	Material	BC 28 x 0.25 mm (Ø) (OFC)
	Section	0.0023 "²
	Number of conductors	2
Insulation	Material	Polyolefin 2.5 mm (Ø)
	Filling	None
Separator	None	
Inner conductor	American Wire Gauge	16 AWG
	Insulation	Colours
	Conductor twisting	Yes
Outer jacket	Material	Polyolefin 7 mm (Ø)
	Colours	Black
		White


Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
CPR Euroclass	Cca-s1b,d0,a1
Flammability test	According EN 60332-1-2
Indoor / outdoor	UV resistant (UL1581, UVA, 720 h)
Smoke emissions	According IEC 61034
Zero halogen compounds	According EN 50267-2-1
	IEC 60754

Mechanical Characteristics:

Temperature range	Mobile installation	- 41 °F till + 176 °F
	Fixed installation	- 59 °F till + 176 °F
UV resistant		Yes

Cross sections:



Electrical Characteristics:

Max. conductor	DC resistance	13.3 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Variants:

- CLS215-CCA/1 - 100 m wooden reel - Black
- CLS215W-CCA/1 - 100 m wooden reel - White
- CLS215-CCA/3 - 300 m wooden reel