

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- 0.30 " (Ø) outer diameter
- Oxygen free copper
- Integrated stereo audio section
- Double Al-foil shielding

Product information:

CLV115 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. A aluminium foil shielding will grant with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected. On one side, the mini jack cable end is 15 cm (projector side) and on the other side (computer side) the mini jack cable end is 50 cm.



Components:

- CableType: SVGA215 - Audio + Video Cable

Properties:



Product Features:

| | |
|-------------|------|
| Application | null |
| Series | null |

Physical Characteristics:

| | | | | |
|-------------------|---------------------|----------------|---------------------------|----------------------|
| Inner conductor | Insulation | Material | FPE 1.55 mm (Ø) | |
| | | Colours | White | |
| | Shielding | Aluminium foil | null | |
| | | Drain wire | BC 7 x 0.12 mm (Ø) (OFC) | |
| | Audio | Insulation | Material | PE 7540 0.7 mm (Ø) |
| | | | Colours | Grey / Purple |
| | | Shielding | Spiral | CCA 28 x 0.12 mm (Ø) |
| Overall shielding | Aluminium foil | | null | |
| | Drain wire | | BC 7 x 0.16 mm (Ø) (OFC) | |
| Outer jacket | Material | | PVC 7.5 mm (Ø) | |
| | Colours | | Black | |
| Type of cable | | | 75 Ω VGA video cable | |
| Inner conductor | Material | | BC 7 x 0.12 mm (Ø) (OFC) | |
| | Audio | Material | BC 10 x 0.12 mm (Ø) (OFC) | |
| Filling | | | Cotton Yarn | |
| Inner conductor | American Wire Gauge | | 28 AWG | |
| Fitted connectors | | | SVGA male | |

Variants:

- CLV115/15 - 15 meter
- CLV115/20 - 20 meter
- CLV115/25 - 25 meter
- CLV115/30 - 30 meter