

Slimline video cable - HDMI 2.0 - HDMI A male - HDMI A male - HighFlex[™]

Highlights:

- · HDMI 2.0 compliant
- null
- Resolutions up to ultra HD 4K 2160p (4096 x 2160) 4:4:4 at 60 Hz
- null
- Semi-Lock™ feature with higher withdrawal force
- · null

Product information:

The CSV210 series are super slim HDMI 2.0 cables, available in lengths from 0.5 m up to 5 m. They are specifically designed for reliable interconnections in professional installations and applications. The ultra-slim construction with a very slim outer diameter offers an elegant solution for office patch usage when installing in narrow installations behind TVs or guaranteeing the best possible airflow in rack applications. They are fully HDMI 2.0 compliant, capable of handling a bandwidth of up to 18 Gbps and resolutions of up to 4K @ 60 Hz 4:4:4. The Semi-Lock™ connector with gold plated contacts design guarantees reliability in all kinds of environments.

Supported standards: High-speed HDMI with Ethernet Supported colors: 16/24bit RGB/YUV, Deep color, x.v. Color, DD+

Supported audio standards: ARC, Dolby Digital Plus, Dolby TrueHD, DTS-HD Master audio, DVD Audio, ... Supported other standards: HDMI Ethernet channel (HEC), 3D, HDCP, CEC, 4K2K (2160i/p), Full HD (1080i/p), HD ready (720i/p), SDTV (480i/p)







Properties:









Product Features:

Application	null
Series	null

Physical Characteristics:

Inner conductor	American Wire Gauge	34 AWG (≤ 2 m)
		32 AWG (3 m)
Outer jacket	Material	PVC 3.8 mm (∅) (≤ 2 m)
		PVC 4.5 mm (Ø) (3 m)
	Colours	Black

Variants:

- CSV210B/0.5 Black version 0.5 meter
- CSV210B/1 Black version 1 meter
- CSV210B/1.5 Black version 1.5 meter
- CSV210B/2 Black version 2 meter
- · CSV210B/3 Black version 3 meter
- · CSV210B/5 Black version 5 meter