

### Highlights:

- HDMI 2.1 full compliant
- Supports 8K @ 60Hz 4:4:4
- 25 AWG
- 48 Gbps data rated
- Semi-Lock™ feature with higher withdrawal force
- Ø 8 mm outer jacket
- Slim connector design
- Sustainable TPE outer-jacket material

### Product information:

The CSV320I is a super slim ultra high speed HDMI 2.1 cable designed for reliable interconnections in professional installations and high performance AV applications. Available in a 5 meter version, it combines next generation bandwidth capabilities with maximum installation flexibility.

The slim outer jacket with an Ø 8 mm diameter and the slim connector design offer an elegant solution for narrow installations behind displays, in furniture, or in rack environments where airflow and space efficiency are essential. Thanks to its HighFlex™ construction and sustainable TPE jacket material, the cable remains durable, flexible, and easy to handle during installation.

Fully compliant with the HDMI 2.1 standard, the CSV320I supports bandwidths up to 48 Gbps and resolutions up to 8K at 60 Hz with full 4:4:4 chroma sampling, delivering ultra sharp visuals, smooth motion, and future ready performance.

The use of high quality 25 AWG conductors ensures stable signal transmission even at ultra high data rates. The Semi Lock™ connector design provides increased withdrawal force for secure and reliable connections in professional environments while maintaining convenient plug and unplug operation.



### Certification:



### Properties:



### Product Features:

Application	null
Series	null

## Physical Characteristics:

---

Inner conductor	American Wire Gauge	25 AWG
Outer jacket	Material	null
	Colours	Black

## Variants:

---

- CSV320IB/5 - Black 'improved' version - 5 meter

PRELIMINARY