

## Highlights:

---

- Triple shielding

## Product information:

---

100 meter reel of 26 AWG-size High quality HDMI cable. If, installed correctly this cable can reach high speeds that live up to the highest HDMI standards. This cable is designed for installation using the PROCAB Contractor Series equipment. Lengths below 8m will perform as HIGH SPEED HDMI with ETHERNET Lengths from 8m until 12m will perform at STANDARD SPEED HDMI with ETHERNET standards. Recommended HD distance : 20 m




## Certification:

---



## Properties:

---



## Inner Conductors:

---



## Shielding:

---



## Product Features:

---

Application	null
Series	null

## Physical Characteristics:

---

Inner conductor	Insulation	Material	FM-PE 1.1 mm (Ø) (5 pair)	
			HD-PE 0.9 mm (Ø) (1 pair)	
			HD-PE 0.9 mm (Ø) (2 cond.)	
Shielding	Aluminium foil	Aluminium foil	null	
		Drain wire	BC 1 x 0.404 mm (Ø) (OFC)	
Overall shielding	Aluminium foil	Aluminium foil	null	
	Drain wire	Drain wire	BC 1 x 0.404 mm (Ø) (OFC)	
	Braiding	Braiding	AL-MG 16 x 12 x 0.12 mm (Ø)	
Outer jacket	Material	Material	PVC 8 mm (Ø)	
	Colours	Colours	Black	
Inner conductor	Material	Material	BC 1 x 0.404 mm (Ø) (OFC) (5 pair)	
			TC 7 x 0.16 mm (Ø) (OFC) (1 pair)	
			American Wire Gauge	26 AWG (5 pair)
			26 AWG (1 pair)	
			26 AWG (2 cond.)	

## Mechanical Characteristics:

---

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 59 °F till + 140 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter