



### Highlights:

- Flexible PVC jacket
- Stranded conductors
- H05VV-F

### Product information:

The PC3G15 and PC3G25 are high quality standard H05VV-F power cables for indoor and outdoor, fixed or mobile use. The cables are made of 3 PVC insulated conductors, with an inner section of 3x1.5mm<sup>2</sup> (PC3G15) or 3x2,5mm<sup>2</sup> (PC3G25). These cables can be used in damp spaces. Packed in a highly flexible PVC outer jacket of 8 mm resp. 9 mm. This offers you a cable that can be used in a wide variety of applications.



### Inner Conductors:



### Product Features:

Application	null
	null

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3 mm (Ø)
		Colours	Blue / Brown / Yellow & Green
Outer jacket	Material	Flexible PVC 8 mm (Ø)	
		Colours	Black
Type of cable	3G1.5 PVC power cable		
Inner conductor	Material	BC 48 x 0.2 mm (Ø) (OFC)	
		Section	0.0023 "²
		American Wire Gauge	16 AWG
		Number of conductors	3

Mechanical Characteristics:

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 77 °F till + 140 °F
Bending radius	Fixed installation	8 x outer diameter
	Mobile installation	8 x outer diameter

Electrical Characteristics:

Lead resistance	1.2 Ω / 100 m
Max. current	16 Amp
Max. operation voltage	300 V

Variants:

- PC3G15/1 - 100 meter