

PC3G25


Power cable - H05VV-F 3G2.5 - 3 x 2.5 mm² - 13 AWG

Highlights:

- Flexible PVC jacket
- Stranded conductors
- H05VV-F

Product information:

The PC3G25 are high quality standard H05VV-F power cables for indoor and outdoor, fixed or mobile use. The cables are made of 3 PVC insulated conductors with an inner section of 3 x 2,5mm². Packed in a highly flexible PVC outer jacket of 9 mm, this offers you a cable that can be used in a wide variety of applications, even in damp spaces.



Inner Conductors:



Product Features:

Application	null
	null

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3.5 mm (Ø)
		Colours	Blue / Brown / Yellow & Green
Outer jacket	Material	Flexible PVC 9 mm (Ø)	
		Colours	Black
Type of cable	3G2.5 PVC power cable		
Inner conductor	Material	BC 48 x 0.254 mm (Ø) (OFC)	
		Section	0.0039 "²
		American Wire Gauge	13 AWG
		Number of conductors	3

Mechanical Characteristics:

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 77 °F till + 140 °F
Bending radius	Fixed installation	8 x outer diameter
	Mobile installation	8 x outer diameter

Electrical Characteristics:

Lead resistance	0.66 Ω / 100 m
Max. current	20 Amp
Max. operation voltage	300 V

Variants:

- PC3G25/1 - 100 meter