

Highlights:


- 11 AWG (4 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant
- EN50399 CPR Euroclass B2ca-s1,d0,a1

Product information:

1 meter sample pack of the CLS240-B2ca. The CLS240-B2ca series are 2-core installation loudspeaker cables compliant to the B2ca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Product Features:

| | |
|-------------|------|
| Application | null |
| | null |
| Series | null |

Physical Characteristics:

| | | | |
|-----------------------|--------------------------|---------------------------|-----------------------|
| Type of cable | 2-core loudspeaker cable | | |
| EN50399 CPR Euroclass | B2ca-s1b,d0,a1 | | |
| Inner conductor | Material | BC 48 x 0.31 mm (Ø) (OFC) | |
| | Section | 0.0062 "² | |
| | Number of conductors | 2 | |
| | Insulation | Material | Polyolefin 4.5 mm (Ø) |
| Filling | None | | |
| Separator | None | | |
| Inner conductor | American Wire Gauge | 11 AWG | |
| | Insulation | Colours | Red / Blue |
| | Conductor twisting | Yes | |
| Outer jacket | Material | Polyolefin 11.7 mm (Ø) | |
| | Colours | Black | |

Electrical Characteristics:

| | | |
|---------------------|--------------------|---------------|
| Dielectric strength | 2 (KV / 1 min. DC) | |
| Rated voltage | 500 V | |
| Max. conductor | DC resistance | 4.95 (Ω / Km) |

Cross sections:

