

PROMO6D-CCT60U-CCA

Sample pack CCT60U-Cca

Highlights:

- 250 Mhz performance, up to 1000Base-T
- "+" Shaped separator to reduce crosstalk
- EN50399 CPR Euroclass Cca-s1a,d1,a1

Product information:

1 meter sample pack of the CCT60U-Cca. The CCT60U-Cca is a CAT6 installation networking cable compliant to the Cca standard of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its improved fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The cable consists of 4 twisted pair cables with solid 23 AWG conductors and a "+" shaped separator. This way, crosstalk and system noise is reduced to a minimum, resulting in higher bandwidth and improved immunity against noise and interference caused by external devices. Providing an optimized solution for 10Base-T, 100Base-TX and 1000Base-T gigabit networks.

More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Product Features:

| | |
|-------------|------|
| Application | null |
| | null |
| Series | null |

Physical Characteristics:

| | | | |
|-----------------------|----------------------|-----------------------------|---|
| Type of cable | | U/UTP CAT6 Networking cable | |
| EN50399 CPR Euroclass | | Cca-s1a,d1,a1 | |
| Inner conductor | Material | BC 1 x 0.56 mm (Ø) (OFC) | |
| | Section | 0.00039 "² | |
| | American Wire Gauge | 23 AWG | |
| | Insulation | Colours | Green / White & Green ; Blue / White & Blue ; Orange / White & Orange ; Brown / White & Brown |
| | Number of conductors | 8 (4 pairs) | |
| | Conductor twisting | Yes | |
| Separator | | + shaped separator | |
| Overall shielding | Aluminium foil | null | |
| Outer jacket | Material | null | |
| | Colours | Black | |

Electrical Characteristics:

| | | |
|--------------------------------------|--------------------------|---------------|
| Max. conductor | DC resistance unbalanced | < 2 % |
| | DC resistance | 8.2 Ω / 100 m |
| Max. Delay / Skew | <45 (ns / 3937.0079 ") | |
| Rated voltage | 300 V | |
| Nom. Velocity of propagation | 69 % | |
| Characteristic impedance | 100 Ω ± 15 Ω | |
| Nom. mutual capacitance | ≤ 5.6 (nF / 100 m) | |
| Pair to ground capacitance unbalance | ≤ 160 (pF / 100 m) | |

Cross sections:

