

Highlights:


- Parallel & separable wires
- 25 AWG stranded conductors
- Braided shielding

Product information:

The RIG series cables are very high quality signal cables for indoor fixed or mobile applications. They have a PVC jacket and are very easy to handle. The tin plated inner conductors are fitted with a durable tin plated copper shielding which gives an excellent protection against interference of all kinds such as electromagnetic fields produced by dimmers, electric motors or power cables. The RIG series cables are "all-round" signal cables which are suited for all kinds of applications where the best reliable signal transmission is needed.



Properties:



Inner Conductors:



Shielding:



Product Features:

Application	null
	null
Series	null

Physical Characteristics:

Inner conductor	Insulation	Material	FPE 1.5 mm (Ø)
		Colours	White / Red
	Shielding	Braiding	TC 16 x 7 x 0.1 mm (Ø) (OFC)
Outer jacket	Material		Flexible PVC 6 x 12 mm (Ø)
	Colours		Black
Type of cable			25 AWG Stereo signal cable
Inner conductor	Material		TC 2 x 14 x 0.12 mm (Ø) (OFC)
	Section		0.00025 "2
	Number of conductors		2 (2 pairs)
	Conductor twisting		Yes

Mechanical Characteristics:

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 77 °F till + 158 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter

Cross sections:

