

Highlights:

- null
- null
- null
- null
- null

Product information:

The PAC151 is a hybrid power/audio cable which can be used in a variety of applications. The cable consists of 3 x 1,5mm² power section and a 2 x 0.22mm² 110 Ohm signal pair. The signal pair can be used for analog audio, digital audio or DMX. The power and signal cable each have a separate jacket which makes it easy to split out the cables at the end.



Components:

- CableType: HMX224 - 24 AWG Balanced signal / DMX-AES cable
- CableType: HPC3G1.5 - 3G1.5 3 x 1.5 mm² PVC power cable

Certification:



Properties:



Product Features:

Application	null
Series	null

Physical Characteristics:

Components		1 x HMX224
		1 x HPC3G1.5
Outer jacket	Material	Highflex PVC 15.9 mm (Ø)
	Colours	Black
Type of cable		Power & 1 x DMX-AES 110 Ω cable
Filling		Non-woven (PET/PA) tape

Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
Flammability test	According EN 60332-1-2

Mechanical Characteristics:

Temperature range	Fixed installation	- 59 °F till + 158 °F
	Mobile installation	- 41 °F till + 167 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter

Variants:

- PAC151/1 - 100 meter
- PAC151/3 - 300 meter

Cross sections:

