

PAC151


Balanced signal / DMX-AES & 3G1.5 Power cable

Highlights:

- null
- null
- null
- null
- null

Product information:

The PAC151 is a hybrid power/audio cable which can be used in a variety of applications. The cable consists of 3 x 1,5mm² power section and a 2 x 0.22mm² 110 Ohm signal pair. The signal pair can be used for analog audio, digital audio or DMX. The power and signal cable each have a separate jacket which makes it easy to split out the cables at the end.




Components:

- CableType: HMX224 - 24 AWG Balanced signal / DMX-AES cable
- CableType: HPC3G1.5 - 3G1.5 3 x 1.5 mm² PVC power cable

Certification:



Properties:



Product Features:

| | |
|-------------|------|
| Application | null |
| Series | null |

Physical Characteristics:

| | | |
|---------------|----------|---------------------------------|
| Components | | 1 x HMX224 |
| | | 1 x HPC3G1.5 |
| Outer jacket | Material | Highflex PVC 15.9 mm (Ø) |
| | Colours | Black |
| Type of cable | | Power & 1 x DMX-AES 110 Ω cable |
| Filling | | Non-woven (PET/PA) tape |


Standards & regulations:

| | |
|-------------------|-----------------------------------|
| RoHS2 compliant | According EU Directive 2011/65/EU |
| Reach compliant | According EC 1907/2006 |
| Flammability test | According EN 60332-1-2 |

Mechanical Characteristics:

| | | |
|-------------------|---------------------|-----------------------|
| Temperature range | Fixed installation | - 59 °F till + 158 °F |
| | Mobile installation | - 41 °F till + 167 °F |
| Bending radius | Fixed installation | 6 x outer diameter |
| | Mobile installation | 8 x outer diameter |

Cross sections:



Variants:

- PAC151/1 - 100 meter
- PAC151/3 - 300 meter