



# Loudspeaker cable - 2 x 1.5 mm² - 16 AWG - HighFlex™

# Highlights:

- Highflex™ solid & flexible jacket
- 1.5 mm<sup>2</sup> (16 AWG) thin and dense stranded conductors
- · 0.30 " (Ø) outer diameter

#### Product information:

The PLS215 is a high quality loudspeaker cable consisting of two 1.5 mm² (16 AWG) conductors composed with 25 copper strands of 0.25 mm thickness. The combination of thin and dense strands with high purity copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket provides great ease of installation for fixed systems while having perfect rolling & amp; unrolling performance for highly demanding mobile applications.



### **Inner Conductors:**



### **Product Features:**

Application null
Series null

# Physical Characteristics:

Type of cable				2-core loudspeaker cable
Inner conductor	Material			BC 25 x 0.25 mm (Ø) (OFC)
	Section			0.0023 "2
	American Wire Gauge			16 AWG
	Number of conductors			2
	Insulation	Material		PVC 2.6 mm (Ø)
	Data	Insulation	Colours	Red / Blue
	Conductor twisting			Yes
Outer jacket	Material			HighFlex™ NBR 0.30 " (Ø)
	Colours			Black


## Mechanical Characteristics:

Temperature range	Fixed installation	- 59 °F till + 158 °F
	Mobile installation	- 41 °F till + 158 °F
Bending radius	Fixed installation	5 x outer diameter
	Mobile installation	10 x outer diameter

## **Electrical Characteristics:**

Max. conductor	DC resistance	13.3 (Ω / Km)
Resistance	Insulation	> 500 M Ω / km
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

### Cross sections:



### Variants:

- PLS215/1 100 meter
- PLS215/3 300 meter