

PRA502

loudspeaker cable - 2-pin speakON - HighFlex™

Highlights:

- Highflex™ solid & flexible jacket
- 2.5 mm² (13 AWG) thin and dense stranded conductors
- 0.31 " (Ø) outer diameter
- Oxygen free copper
- 60 mm transparent shrink sleeve

Product information:

The PRA502 is a high quality loudspeaker cable constructed using the PLS225 cable and fitted with two Neutrik 2-pin speakON (NL2FX) connectors. The cable consists of two 2.5 mm² (13 AWG) conductors composed with 224 copper strands of 0.12 mm thickness. The combination of thin and dense strands with high purity copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding mobile applications. An attached shrink sleeve allows custom labeling for easy identification. The cable comes in different lengths from 1.5 meters to 20 meters.

Components:

- CableType: PLS225 - Loudspeaker cable - 2 x 2.5 mm² - 13 AWG - HighFlex™
- Connector: NL2FX - 2 pole cable connector, chuck type strain relief



Certification:



Properties:



Product Features:

Application	null
Series	null

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3.2 mm (Ø)
		Colours	Red / Blue
Outer jacket	Material	Durable PVC 8 mm (Ø)	
		Colours	Black
Type of cable	2-core loudspeaker cable		
Inner conductor	Material	BC 224 x 0.12 mm (Ø) (OFC)	
		Section	0.0039 "²
		American Wire Gauge	13 AWG
		Number of conductors	2
Connection type	SpeakON Female to Female		
Fitted connectors	2 x Neutrik NL2FX		

Mechanical Characteristics:

Temperature range	Fixed installation	- 68 °F till + 158 °F
	Mobile installation	- 41 °F till + 158 °F
Bending radius	Fixed installation	5 x outer diameter
	Mobile installation	10 x outer diameter

Electrical Characteristics:

Lead resistance	0.8 Ω / 100 m
-----------------	---------------

Wiring Diagrams:

