

PRA504

loudspeaker cable - 4-pin speakON - HighFlex™

Highlights:

- Highflex™ solid & flexible jacket
- 4 conductors for 2-channel loudspeaker connection
- 0.43 " (Ø) outer diameter
- Oxygen free copper
- 60 mm transparent shrink sleeve

Product information:

The PRA504 is a high quality loudspeaker cable constructed using the PLS425 cable and fitted with two Neutrik 4-pin speakON (NL4FX) connectors. The cable consists of four 2.5 mm² (13 AWG) conductors composed with 224 copper strands of 0.12 mm thickness. The combination of thin and dense strands with high purity copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding mobile applications. An attached shrink sleeve allows custom labeling for easy identification. The cable comes in different lengths from 1.5 meters to 20 meters.

Components:

- CableType: PLS425 - Loudspeaker cable - 4 x 2.5 mm² - 13 AWG - HighFlex™
- Connector: NL4FX - 4 pole cable connector, chuck type strain relief



Certification:



Properties:



Product Features:

Application	null
Series	null

Physical Characteristics:

Type of cable		4-core loudspeaker cable	
Inner conductor	Material	BC 224 x 0.12 mm (Ø) (OFC)	
	Section	0.0039 "²	
	Insulation	Material	PVC 3.2 mm (Ø)
		Colours	Black / Red / Blue / Yellow
Number of conductors		4	
American Wire Gauge		13 AWG	
Fitted connectors		2 x Neutrik NL4FX	
Outer jacket	Material	Durable PVC 11 mm (Ø)	
	Colours	Black	
Connection type		SpeakON Female to Female	

Mechanical Characteristics:

Temperature range	Fixed installation	- 68 °F till + 158 °F
	Mobile installation	- 41 °F till + 158 °F
Bending radius	Fixed installation	5 x outer diameter
	Mobile installation	10 x outer diameter

Electrical Characteristics:

Lead resistance	0.8 Ω / 100 m
-----------------	---------------

Wiring Diagrams:

