

## Highlights:

---

- Ultraflex™ Ultra flexible jacket
- 24 AWG thin and dense stranded conductors
- 0.26 " (Ø) outer diameter
- Oxygen free copper
- 60 mm transparent shrink sleeve
- Gold contacts, scratch resistant black shell

## Product information:

---

The PRA610 is a high-quality microphone cable constructed using the ultra flexible PMC224 cable and fitted with Neutrik NP3X-B (gold contacts, black jack shell) connectors. The 24 AWG (0.22 mm<sup>2</sup>) thin & dense stranded bare copper conductors are surrounded by a high coverage spiral shielding. In combination with the thick and soft PVC outer jacket, this provides a flexible but solid feel. The high-purity copper, high-coverage shielding and low capacitance guarantee an optimal signal transmission. The attached shrink sleeve allows custom labeling for easy identification. It comes in 2 lengths of 1.5 meters and 3 meters, providing solutions for all applications.



## Components:

---

- CableType: PMC224 - Balanced microphone cable - flex 2 x 0.22 mm<sup>2</sup> - 24 AWG - UltraFlex™
- Connector: NP3X - 3 pole 1/4 inch professional phone plug



## Certification:

---



## Properties:

---



## Product Features:

---

Application	null
Series	null

## Wiring Diagrams:

---



## Variants:

---

- PRA610/1.5 - 1.5 meter
- PRA610/3 - 3 meter